
Coal: A Neglected Resource - Making the Best of it for the Future

27th Annual Review Conference
Keynote Paper
Pittsburgh June 6, 2006

Ari Geertsema
University of Kentucky Center for Applied Energy Research



Overview

1. Coal through the ages
2. Uses of coal with R&D indicated
 - 2.1 Power Generation
 - 2.2 Gasification
 - 2.3 Liquefaction
3. Projections
4. Conclusions




1. Historical



- Charcoal used for pig iron
- Deforestation caused switch to coal
- 1620 coke oven production first recorded
- 70% of global steel now depends on coal

- Coke: a Chinese article of trade > 2000 years ago
- Coal probably used in the iron ages
- 13th century coal used in England for forging iron



- 1792 Murdoch proved gas can be generated from coal
- Town Gas : London 1814




Coal Chemistry



**Glauber's "Philosophical Oven"
1652**


**Dry coal distillation
(tars, oils, aromatics, char)**

**Up to middle 1800's coal tar
regarded as waste**



Coal Chemistry

- Dyestuffs: the roots of organic chemical synthesis
- Perkin 1856: “aniline purple”
- 50,000 dyes by 1900
- 1913 Germany controlled 90% of coal derived dyes
- Start of multinational petrochemical companies
- Coal science developed in its own right
- Analytical chemistry made big strides



Other Coal Based Spin – Offs

- Creosote for railway ties
- “Tar asphalt” for roads
- Technical carbon for electrical/ electronic applications
- Carbon black in tires since 1912
- Graphite plates for chlor-alkali industry
- Activated carbons
- Derivative chemicals: fertilizers, acetic acid, acetates, methanol, solvents, lubricants
- Phenolics and cresylics
- US Coal tar now less than 1/3 of 1950 production



2. Main Uses of Coal

- Combustion to produce steam/power
- Gasification to produce syngas (H_2 with CO)
 - Syngas to fuels (Indirect Liquefaction)
 - Syngas to chemicals, including methanol
 - Syngas to hydrogen
 - Syngas to synthetic natural gas (SNG)
- Direct coal liquefaction (Not covered here: not commercial)
- Co-production (“polygeneration”)
- Gas to Liquids (GTL) same as second part of Coal to Liquids (CTL)
- Industrial uses – steel etc (not covered further)




USA Situation

- National Coal Council Report March 2006
<http://www.nationalcoalcouncil.org/>
- USA has 27% of the world's coal reserves
- Power generation from coal dominates
 - 52% of US power is from coal
 - 91% of mined coal goes to power generation



Coal Flow in the USA




Source: 2006 EIA Outlook



Energy Prices 1980 – 2030

2004 \$/Million Btu



Source: 2006 EIA Outlook



Coal Use Grows While Emissions Decline

Coal Used for Electricity Has Tripled
Since 1970 While Emissions Have Been Significantly Improved




Figure ES.2 Source: EPA National Air Pollutant Emission Trends Dec 2004; EIA Annual Energy Review 2003 (September 2004)



2.1 Power Generation


- Few coal fired power stations built in recent past – gas believed to be cheap, plentiful and clean
- Future: carbon taxes and global warming issues critical
- Nuclear power for power generation (currently about 20%) likely to increase but slowly
- More recent combustion technologies:
 - supercritical and ultra-supercritical steam systems for high efficiencies
 - fluidized bed combustors
 - circulating fluidized bed units



U.S. Forecasts Largest Increase in Coal Generation in Decades

Planned Coal-Fueled Plants Represent 280 MTPY

of Coal Use



* Timing not yet committed.

Figure ES.3 Source: DOE, National Energy Technology Laboratory, 2006




R&D Needs Related to Coal Fired Power Generation

- Environmental improvement
- Efficiency improvements
- Construction materials for high temperatures and pressures
- Sensors and controls
- Ash disposal and utilization
- Further development and commercialization of IGCC (Integrated Gasification Combined Cycle) systems, including turbines
- Fuel cells as co-producing units
- See DOE and CURC Roadmaps and web sites



Combustion and Gasification

Gas Composition as fn (O_2 /Coal)




2.2 Gasification

- Sub-stoichiometric combustion: leads to $\text{CO} + \text{H}_2$ (“Syngas”)
- Many different commercial gasifiers applied world-wide but few built in the USA so far (Four facilities)
- For power generation: growing interest in IGCC for clean power generation with CO_2 capture potential
- Syngas a very versatile building block:
 - Methanol, DME, Acetates, Olefins etc
 - Fischer-Tropsch products; fuels and chemicals
 - H_2 , NH_3 , Fertilizers
 - SNG via methanation



Basic Gasification Flowsheet



Source: GTC web site



Main Gasifier Types

1. Moving Bed


- Dry Bottom shown (Lurgi)
- Slagging Bottom as a variation (BGL)

2. Fluidized Bed

(Winkler and others)

3. Entrained – Slagging

(GE/Texaco, E-Gas, Shell)




R&D for Gasification

- Refractories
- High temperature materials of construction
- Control systems
- Novel (cheaper) concepts
- Lower cost of producing syngas
- Feed systems: all coal grades; biomass; wet and dry
- Slag removal and application/uses for by-products
- Heat integration systems
- Turbine developments
- Improved gas clean-up: H_2S , COS , Hg , CO_2 and particulates
- Syngas to synthetic natural gas through methanation
- Entry into large scale hydrogen production



2.3 Coal Liquefaction: Two Methods



Direct: fine low-ash coal with catalyst; high pressure (3500psi/230 bar+) and temperature (750°F/400°C) reacts with hydrogen to produce liquid hydrocarbons and char-like residue

Indirect: coal gasified with steam and oxygen and resultant CO and H₂ (syngas) is catalytically converted to liquid hydrocarbons at about 375psi (25 bar) and 400-630°F (200-340°C)



Indirect Liquefaction: Fischer-Tropsch

- Invented 1920's
- South Africa saw opportunity in late 1920's
- Developed pre WW II Germany
- Sasol commercialized FT in South Africa 1955 and again 70's and 80's: only commercial CTL in the world and expanded into chemicals to improve profitability
- Other ventures built based on natural gas (GTL), Shell, PetroSA
- Sasol experience of 50 years: >200 different products; cumulatively >1.5 billion barrels of fuel; Synfuels 28% of South African transportation fuels demand.
- Coal based: commercially less attractive for new investments than gas based



Sasol Plants At Secunda ~ 1985



Initial capacity: 2 x 50,000 bbl/d, Then 40% of SA's fuel needs, now 28%; Cost \$6bn; Site ~3,200 acres
Two plants built sequentially with \$500m saving
Construction work force 28,700; 250 million man-hours.
Now 160,000 bbl/d



Sasol GTL Oryx Project in Qatar



- Two reactors 60 m high, 10 m diameter; @2,200 tons
- Project expansion to add 66,000 bbl/d fuels and 8,500 bbl/d lubricants
- 34,000bbl/d plant to be commissioned June 6, 2006



R&D: FT Product Work-up

Final product spectrum:

- Depending on type of reactor and catalyst, the products can be primarily diesel or gasoline and chemicals with a wide range of options
- Can be adjusted in wide ranges but need to be set more narrowly at engineering design stage
- Potential for value addition: preferably as spin-offs and not as part of key base load justification
- Market driven product spectrum – use for naphtha
- Modeling aspects of the FT system and the overall highly integrated production process with extensive utility and power generation options



R&D Aspects of CTL

Products: Diesel

- Generically: Primary product zero S, minimal aromatics
- Predominantly straight chain (high cetane number >70)
- Fuels fully compatible with existing fuels: logistics and infrastructure advantages for FT fuels
- Suitable for aviation/jet fuels
- Potentially a high H₂ content energy carrier
- Emission from diesel engines but greatly superior to even CARB diesel performance
- Excellent blending stocks
 - ➔ Potential for niche and bulk product applications research



Economics: Capital Cost: R&D Impact

CTL capital investment (Sasol 2006)

For 50,000 to 80,000 bbl/d green field cost
\$60,000 to \$80,000 per daily barrel (\$3 to \$6
Billion) – But: site specific

(Note: GTL ~\$30,000/dbbl)

Production costs

Can produce finished products at about \$45-
\$50/bbl (crude equivalent: \$35-40/bbl)

Yields: Typically 2 barrels per ton, depending on coal
i.e. for 80,000 bbl/d about 15 million t/year coal

➔ R&D can reduce capital costs through reduction
of capital investment, e.g. construction materials,
control systems, plant integration/optimization



Why the Great Interest in CTL in the US Today?

- Supply and demand of liquid fuels internationally very tight – China and India; declining reserves
- Consequently high gasoline prices
- Crude oil supply from high risk locations
- Coal prices increased, but coal much cheaper than other energy sources
- Abundant coal reserves
- Potential entry to the hydrogen economy via gasification



Some Hurdles to CTL Commercialization

- Hurdles are not insurmountable: can be done again and can make money
- Energy Policy Act of 2005 a point of departure - Government facilitates and provides incentives
- Economic uncertainty and perceived high risk for high capital layout
- More plants required to obtain comfort for financiers
- Large companies reluctant to lead commercialization
- Many studies done but inadequate open literature data on actual plants available to validate economics
- Some lessons are only learnt at large scale
- It requires a national will and strategy
 - ➔ Economic concerns dominate but R&D can contribute to improved viability



3. Projections to 2025: NCC Report

Capital Expenditures for Coal Btu Conversion Technologies

	Coal Use Per Year in Million Tons	Capital Expenditures in Billions (2005 Dollars)
Coal-to-liquids	475	\$211
Coal-to-gas	340	115
Coal-to-electricity	375	150
Coal-to-hydrogen	70	27
Coal for ethanol	40	12
TOTAL	1,300	\$515

Figure ES.5

Current coal production about 1.1 billion t/year

Additional needs 1.3 billion t/year

Economic multiplier: Over next 20 years it will contribute to

- 1.4 million new jobs
- GDP gains of \$3 trillion

Some concerns:

Impact on mining

Impact on the environment

Transportation of coal

Skills



4. Outlook for Coal Research

- Coal as an abundant resource will be used for many years: we need responsible ways of doing it
- Environmental aspects, including CO₂ capture and sequestration are key to the success with consideration of efficiency, conservation and stewardship: “Cradle to grave”
- Understanding the fundamentals of coal chemistry can lead to new applications and materials
- Chemistry, catalysis and material science underpin much of the research needed
- Enabling research should lead to new technological options
- Better understanding of fundamentals and modeling lead to process and design optimization and cheaper products
- Additional research provides a greater pool of very necessary human resources in this area



Action

Step out and take on the challenges which the current circumstances offer us to use coal cleanly and efficiently:

Research and

Development and

Demonstration and

Deployment/Commercialization

➔ Accelerate the pace

